

301-CI9501-0000

Multi-Conductor – Shield Twisted Pair Cable







DECRIPTION

16 AWG stranded (19x29) tinned copper conductor, polyethylene insulation, twisted pair, aluminum shield (125% coverage), 18 AWG stranded tinned copper drain wire, PVC jacket.

APPLICATION

Multipair Audio, Control and Instrumentation Cable for Industrial, Data, Interconnect and Analogue Audio used.

PHYSICAL CHARACTERISTICS

Conductor

AWG

| Pair | AWG | Stranding | Conductor Material |
|------|-----|-----------|--------------------|
| 1 | 16 | 19x29 | TC – Tinned Copper |

Insulation

Insulation Material

| Insulation Material | Wall Thickness (mm) |
|---------------------|---------------------|
| PE – Polyethylene | 0.81 |

Outer Shield

Outer Shield Material

| Туре | Outer Shield Material | Coverage |
|------|-----------------------|----------|
| Tape | Aluminum Mylar | 125% |

Outer Shield Drain Wire AWG

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 18 | 16x30 | TC – Tinned Copper |

Outer Jacket

Outer Jacket Material

| Outer Jacket Material | Nom. Wall Thinkness (mm) | | |
|---------------------------|--------------------------|--|--|
| PVC – Polivinyl Choloride | 0.81 | | |

Overall Cabling

Overall Nominal Diameter: 7.9 mm

Pair

Pair Color Code Chart

| Number | Color | |
|--------|---------------|--|
| 1 | Black & Clear | |



Mechanical Characteristics (Overall Cable)

| Operating Temperature Range | -20°C to 80°C | |
|-----------------------------|---------------|--|
| Temperature Rating | 80°C | |
| Max Pulling Tension | 46 Kg | |
| Min. Bend Radius | 76.2 mm | |

Applicable Specifications and Agency Compliance (Overall Cable)

Applicable Standards

| EU CE Mark (Y/N) | Yes |
|--------------------------------------|-----|
| EU Directive 2002/95/EC (RoHS) (Y/N) | Yes |
| EU RoHS (Y/N) | Yes |

Electrical Characteristics (Overall Cable)

Nom. Characteristic Impedance

| Impedance (Ohr | n |) |
|----------------|---|---|
| 65 | | |

Nom. Inductance

| Inductance (μH/ft) |
|--------------------|
| 0.2 |

Nom. Capacitance Conductor to Conductor

| Capacitance (pF/ft) | |
|---------------------|--|
| 23 | |

Nom. Capacitance Cond. to Other Conductor & Shield

| Supusitarios Soriai to Strici |
|-----------------------------------|
| Capacitance (pF/ft) |
| |
| $\Lambda\Lambda$ |

Nom. Conductor DC Resistance

| DCR@20°C (| (Ohm/1000ft) |
|------------|--------------|
| 4 | 5 |

Max. Operating Voltage

| poraning ronago |
|---------------------|
| Voltage |
| 600 |

Max. Operating Current

| С | urrent/Cond. @ 25°C | |
|---|---------------------|--|
| | 7A | |

Part Number

301-Cl9501-0000 1 Pair 16 AWG Shielded Twisted Cable



Product Family

| 301-CI9502-0000 | 2 Pair 16 AWG Shielded Twisted Cable |
|-----------------|---------------------------------------|
| 301-Cl9504-0000 | 4 Pair 16 AWG Shielded Twisted Cable |
| 301-Cl9510-0000 | 10 Pair 16 AWG Shielded Twisted Cable |

© Alantek Communications USA All Right Reserved.

Alantek® Communications USA 2006. This information provides a general description of product and shall not form part of any contract. Improvement or changes may be made to the product without advanced notification.